



Pendant Speakers

MAT # 700286198 (Black) / 700286206 (White)

Technical Specifications

Frequency Response (-10 dB)*:	60 Hz to 19 kHz
LF Driver:	6-1/2" MDT Metal-Alloy Cone
HF Driver:	20 mm (3/4") Polycarbonate Dome
Sensitivity (1W/1 M):	89.5 dBspl (Average 100 Hz - 10 kHz)
Impedance Ratings:	Low (16 ohms) / High (70V/100V)
Power Input (Max.):	100W @ 16 ohms; 32W @ 70V/100V
Power Settings (in watts)†:	70V: 32, 16, 8, 4, 2, 1 100V: 32, 16, 8, 4, 2
Enclosure Material:	ABS
Grille Material:	Powder-Coated Perforated Metal
Terminations:	4 Terminal Snap-Lock Input Connector
Product Weight:	10 lb.
Speaker Dimensions:	15" dia. x 9-1/4" D
Included Accessories:	(1) Snap-Lock Input Connector; (1) Quick-Snap Clip (2) Cable Kits; (3) Nuts; and (3) Suspension Cables with Forged Eye Bolts
Enclosure Finish & Color:	Textured White or Black

* Free Space Response, 16-ohm input.

† Front panel, switch-selected.